

A MORE DURABLE AND SUSTAINABLE IBC SOLUTION

The TUFF Stack Delivers a Robust, Sustainable, and Reusable IBC

FEATURES AND BENEFITS

- **Rigid & Reliable Strength:** UN/DOT certified Title CFR 49 UN31H1 for Packing Groups II and III for hazardous materials. Rotationally molded using industrial grade corrosion-free HDPE to have thick, durable walls and high impact strength.
- **Easy to Use:** Molded-in and inked volume markers are added for approximate filling and product level monitoring. The sloped bottom maximizes drainage, reducing product waste. The valve area is easily accessible by operators, and TUFF Series totes stack seamlessly with other brands.
- **Cost Efficient & Low Impact:** Returnable IBC tanks are constructed for reuse over many years, designed for multiple and repeated turns. Investing in a fleet of asset tanks delivers a higher ROI and reduces waste compared to one-way containers.

SPECIFICATION CHART

MODEL	SIZE	TARE WT
120 Gallon	45" x 45" x 36"	189 lbs
220 Gallon	45" x 45" x 48"	227 lbs
275 Gallon	45" x 45" x 56"	244 lbs
330 Gallon	45" x 45" x 64"	267 lbs

UN/DOT certified, Title CFR 49 UN31H2, 1.9 specific gravity, measured in gallons and liters. All dimensions and tare weights are approximate.

TUFF LINQ® VALVE

- Integrated cam-lock provides superior seal to prevent leaks
- Patented valve with 30% stronger connection
- Large external threading reduces risk of contamination



U.S. Patent 11,713,238

Interlocking Stacking
Design, 2-3 High

6" Top Fill Lid with
(2) 2" Top Ports

Optional Molded-In
Company Logo

Molded-In & Marked
Volume Markers

Made from HDPE,
FDA-Compliant Prime
Virgin Resin

Multiple Base Color Options

2" TUFF LinQ Outlet Valve

Integrated Anti-Teeter Bars

4-Way Forklift & Pallet
Jack Access



INDUSTRIES WE SERVE



Agricultural



Industrial
Chemicals



Metal
Treatment



Oil & Gas



Paint &
Coatings



Water
Treatment

